

220

MASKING



Physical Properties

Backing: Saturated semi-crepe paper 60 g/m², (110 µm)

Color: Ivory or yellow

Adhesive: Natural rubber and cross linked resins

Total thickness: 130 µm

Adhesion to steel: 260 gr/cm

Tensile strength: 4 Kg/cm

Elongation at break: 9%

Temperature use range: 60 °C

Storage recommendation

Store the tape preferably horizontally, under normal conditions of 15-30 °C and 50% R.H., in the original carton and in a dry place.



Description

- ▶ Saturated semi-crepe paper pressure sensitive adhesive tape, ivory or yellow, designed for masking applications.

Typical Applications

- ▶ Masking tape to be used at average temperatures. Used in industry, building and other difficult jobs, where a pressure sensitive adhesive tape is needed.

Features

- ▶ Saturated crepe paper
- ▶ Natural rubber and cross linked resins

Properties

- ▶ High conformability
- ▶ Compatible with solvent and water paint
- ▶ Easy tear
- ▶ Good mechanical strength
- ▶ Instant adhesion, sticks to a wide range of surfaces
- ▶ Solvent and thinner resistant
- ▶ No adhesive transfer

Benefits

- ▶ Easy application on curved profiles and irregular surfaces
- ▶ Clean and precise removal
- ▶ Practical use without waste
- ▶ Does not unstick during use
- ▶ No cleaning activities after use



Europe

Tel.: +39 0142 413 222

Fax: +39 0142 413 265

e-mail: tapesdivision@vibac.it

www.vibacgroup.com

MASKING

natural rubber