

**WMH311****High Quality White Double Coated PE Foam Tape****DESCRIPTION**

A white 67Kg Polyethylene Double Coated Foam Tape, coated on both sides with Hot Melt Rubber resin adhesive; suitable for general purpose mounting applications and conversion to pads.

**TECHNICAL DATA**

|                    |               | (T10/00)<br><u>1mm thick</u> | (T11/00)<br><u>2mm thick</u> |
|--------------------|---------------|------------------------------|------------------------------|
| Thickness          | : Liner       | 0.125 mm                     | 0.125 mm                     |
|                    | : Carrier     | 1.00 mm                      | 2.00 mm                      |
|                    | : Total       | 1.125 mm                     | 2.125 mm                     |
| Peel Adhesion      | : Open Side   | 1000 n/m                     |                              |
|                    | : Closed Side | 1000 n/m                     |                              |
| Tack               | : Open Side   | 900 n/m                      |                              |
|                    | : Closed Side | 900 n/m                      |                              |
| Release from liner | :             | 10 n/m                       |                              |
| Shear 23C          | :             | 25 mm x 25 mm @ 1kg 400 hrs  |                              |
| Service Temp.      | :             | -10 to 60 Degrees °C         |                              |

**NOTE**

Unless otherwise indicated, the figures above are average values and should not be treated at face value for specification purposes. The Company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modification or otherwise. Please check that you have the latest issue of the information sheet. All slitting and length tolerances are to British Standards, but other tolerances are available by request.